

## MSD 6" Series

### Manual Sidedrive Dual Mast

The BestPack™ 6" Series Semi-Automatic Uniform Tape Carton Sealer is an operator fed adjustable carton sealer using 6" wide tape to seal the top and bottom of a carton. 6" wide tape helps with security, tamper protection, and pilferage prevention, and also effectively seals cartons that are overly heavy, over-filled, or otherwise difficult to keep sealed.

All systems incorporate our exclusive pop out pressure sensitive "High Speed" tape heads with patented tab adjustment, and the dual (telescopic) masts allow for an extra 4" carton height extension on the upper assembly.

All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance. The MSD 6" series sealer also accepts 4", 3" and 2" tape heads with optional skid plate adapters.



## Key Points of the Carton Sealer



Operator Fed



Uniform Cartons



Top & Bottom Seal

## Features

- Heavy Duty 2mm CNC Cut and Welded Frame Including Upper Welded Legs
- Side Belt Drive System with Idler Rollers Behind the 1-piece Die Molded Belts that also Includes V-belt Guide
- Accepts 6", 4", 3", and 2" Pop-out BestPack High Speed Tape Heads
- Telescopic Mast Design with Screw Drive Shafts and a Unique 4 Roller Upper Side Compression Unit
- Width and Height Adjustment Crank Handles can be Mounted on Either Side of the Sealer
- Electrical On/Off Box can also be Easily Mounted on Either Side of the Sealer (Left Side is Standard)
- Adjustable Bed Height for the MSD22-6 is 23.5" to 30.0"
- Tape Roll Lengths: 1,000 yd. and 1,500 yd.

- Upper Telescopic Mast is Tapped and Drilled that can be Raised (Un-bolted, Raised and Re-bolted) for an Extra 4" Carton Height if Needed
- Quality UL Approved Electrical Parts

## Options

- Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Heavy Duty Dual Locking Casters
- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- 3 Flap Folder
- Interlock Safety Gates
- Motorized Height and/or Width Adjustment
- Food Grade 304 Stainless Steel

# Extra Accessories to Improve Efficiency



Spare Parts Kit



Locking Casters



Long Infeed/Exit Conveyor  
w/ L-Bracket



Spare Tape Head

- High Speed Motor Upgrade (Up to 125 ft.)
- 3 Flap Folder
- Food Grade 304 Stainless Steel
- Short Infeed/Exit Conveyor w/ L-Bracket
- Carton Sealing Tape

## Machine & Carton Specifications

**110 Volts 60 Hz**  
Power Requirements

**Up to 40 Cartons/min.**  
Speed

**None**  
Air Requirements

**425 lbs**  
Shipping Weight

Model	Machine Dimensions Length x Width x Height	Carton Range* Length (min. - max.) x Width (min. - max.) x Height (min. - max.)	Conveyor Height Adjustment Height (min. - max.)	Cartons per min.	Shipping Weight (lbs.)
MSD22-6 <b>6" Tape Head</b>	(39.5") x (32.8") x (70.3")	(6.0" - U) x (8.25" - 20.0") x (3.5" - 20.5")	(23.5" - 30.0")	Up to 40	425
MSD22-6M** <b>6" Tape Head</b>	(39.5") x (32.8") x (70.3")	(6.0" - U) x (8.25" - 20.0") x (3.5" - 20.5")	(23.5" - 30.0")	Up to 40	425

Information subject to change without notice.

U - Unlimited

\* Outside Dimensions Only

All Models available in High Speed & Food Grade 304 Stainless Steel

\*\* Motorized assist tape heads when high speed motors and/or acrylic tapes are used