

CAN/BOTTLE UNITIZING SYSTEMS

SBC-932 Side-Seal Strapping Machine



Features

- Reliable VK20 Strapping Head
- Pendant mounted machine controls for access on either side of the machine
- Space-saving machine-mounted dispenser
- Indexing strapping head to ensure tight strap application
- Out-of-strap indicator
- 'Crash-proof' bayonet cylinder prevents damage to bayonet
- Available with three-strand and five-strand chain conveyor and integrated pallet turntable
- Optional reciprocating bayonet bottom track
- Optional under-feed and bayonet tracks

SBC-932 II

Automatic Side Seal Strapping Machine

Standard Features

The SBC-932 Fully Automatic Strapping System is ideal for bulk loads of containers. There are 4 compression choices available to provide the best package for your application.

The SBC-932 features the fast and reliable VK-20 strapping head. The heavy duty heater knife has a cycle life in excess of 900,000 cycles, which insures strong consistent welds and low maintenance. Independent motors, which simplify maintenance and eliminate the need for multiple clutch assemblies drive the major functions of the VK-20 head.

Options

- Free Standing Compression Units: 500 lbs., 1,200 lbs. or 4,000 lbs.
- Strap Track Underfeed
- Multi-Strand or Roller Conveyor with or without Turntable
- Audible out of Strap Indicator
- Light Beacon Alarm System
- Powered Head Float for Glass Applications

Specifications

Electrical:	460V, 3ph, 60hz
: r i A	i s p 0 8
Strapping	Polyester
Strap Size:	3/8" (9 mm) - 3/4" (19 mm)
Package Sizes	*Standard - Height 26" min. up to 110" max. Width 40" min. up to 60" max.
Conveyor Height	*Standard - 9" up to 20"

*Alternative track sizes and conveyor heights are available.

