

Shanklin[®] Model S24B/S24BL

The Heavy Duty Semi-Automatic L-Sealer Series



- Automatic sealing cycle
- Power film unwind
- Easy loading film inverting head
- Left-to-right or right-to-left product flow
- Easy access electrical controls
- Automatic package discharge
- Brush backed pin perforator
- Hot knife seal system


The Shanklin® S-series wrappers; quality comes standard

Description


The Shanklin Model S24B/S24BL L-Frame Sealer is high production semi-automatic wrapping machine. Features of the machine include a 3-point sealing arm suspension with air-magnetic latching, fool-proof arm safety, a precisely controlled heat sealing cycle and a timer-controlled discharge conveyor. Electrical relays are mounted on a U.L. listed panel located behind the easy-to-reach control panel which provides accurate heat for consistent seal. For operator convenience, the unit is equipped with telescoping legs.

Higher production speeds are achieved with the Model S24B/S24BL because it includes several unique features normally found only on our fully automatic L-Sealers; namely, the power film unwind and the film inverting head. The power film unwind permits a free feeding of the film, thus increasing operator efficiency. In addition, better seals (fewer rewraps) are obtained because the film in the seal area is always loose.

S24B Plan View



S24BL Plan View



Shanklin Model S24B/S24BL Specifications

	Model S24B/S24BL
Special Features	<ul style="list-style-type: none"> • Power Film Unwind • Film Inverting Head • Brush Backed Pin Perforator • One Piece Hot Knife
Sealer Size	15" Wide x 33" Long
Machine Height	Adjustable from 31" to 43"
Floor Space	4 1/2' X 7'
Package Speeds	20 to 30 Packages/Min.
Power	220V, 20 Amps, 1 Phase (U.L. Listed Control Panel)
Compressed Air	0.5 C.F.M. at 50 P.S.I
Mechanical Adjustments	<ul style="list-style-type: none"> • Discharge Conveyor Height • Packing Table and Inverting Head Depth • Package Guide Position • Film Roll Guides • Machine Height
Electrical Controls	<ul style="list-style-type: none"> • "Seal" and "Open" Switches • Dwell Timer • Conveyor Timer • Power Unwind Reversing Switch
Pneumatic Controls	<ul style="list-style-type: none"> • Flow Control Valves on Sealing Arm • Air Filter • Lubricator • Regulator • Gauge
Safety Features	<ul style="list-style-type: none"> • Automatic Force Sensor and switches on Seal Jaw provide redundant safety benefits in the event resistance were encountered during closing and prior to locking
Accessories	<ul style="list-style-type: none"> • Adjustable Depth Inverting Head • Adjustable Height Inverting Head • Teflon Coated Inverting Head • Special Parts for 18" or 20" Width Capability Available • Scrap Removal System (Vacuum or Winder) • Static Eliminator • Film Centerfolder • Casters

Distributed by:



Shrink Packaging
100 Westford Road
Ayer, MA 01432
978-772-3200 Fax: 978-772-5660
www.shanklincorp.com

Our Products Protect Your Products®

Corporate Office: Sealed Air Corporation
200 Riverfront Boulevard, Elmwood Park, NJ 07407 USA
www.sealedair.com

© Reg. U.S. Pat. & TMOff. © Sealed Air Corporation (US) 2010. All rights reserved. Printed in the U.S.A. The "9 Dot Logo" and "Sealed Air" are registered trademarks of Sealed Air Corporation (US).

rev 9/7/10